



物料编号	规格	导体结构	外径下限 mm	外径上限 mm	近似重量 kg/km	导体电阻 Ω/km
AN018.020.01.000.75B	1x075	27/0.19	1.7	1.9	4	43.6
AN018.020.01.001.00B	1x1.00	35/0.19	1.9	2.1	5	32.7
AN018.020.01.001.25B	1x1.25	25/0.25	2.1	2.3	6	24.8
AN018.020.01.001.50B	1x1.50	31/0.25	2.2	2.4	7	21.2
AN018.020.01.002.00B	1x2.0	41/0.25	2.5	2.8	9	15.7
AN018.020.01.002.50B	1x2.5	51/0.25	2.7	3	12	12.7
AN018.020.01.003.00B	1x3.0	61/0.25	3.1	3.4	14	10.2
AN018.020.01.004.00B	1x4.0	82/0.25	3.4	3.7	17	7.85
AN018.020.01.005.00B	1x5.0	102/0.25	3.9	4.2	19	6.57
AN018.020.01.006.00B	1x6.0	123/0.25	4	4.3	23	5.23
AN018.020.01.008.00B	1x8.0	64/0.4	4.6	5	29	3.97
AN018.020.01.010.00B	1x10.0	77/0.4	5.3	6	43	3.03
AN018.020.01.012.00B	1x12.0	96/0.4	5.8	6.5	50	2.53
AN018.020.01.016.00B	1x16.0	126/0.4	6.4	7.2	63	1.93

物料编号	规格	导体结构	外径下限 mm	外径上限 mm	近似重量 kg/km	导体电阻 Ω/km
AN018.020.01.000.75B	1x075	27/0.19	1.7	1.9	4	43.6
AN018.020.01.001.00B	1x1.00	35/0.19	1.9	2.1	5	32.7
AN018.020.01.001.25B	1x1.25	25/0.25	2.1	2.3	6	24.8
AN018.020.01.001.50B	1x1.50	31/0.25	2.2	2.4	7	21.2
AN018.020.01.002.00B	1x2.0	41/0.25	2.5	2.8	9	15.7
AN018.020.01.002.50B	1x2.5	51/0.25	2.7	3	12	12.7
AN018.020.01.003.00B	1x3.0	61/0.25	3.1	3.4	14	10.2
AN018.020.01.004.00B	1x4.0	82/0.25	3.4	3.7	17	7.85
AN018.020.01.005.00B	1x5.0	102/0.25	3.9	4.2	19	6.57
AN018.020.01.006.00B	1x6.0	123/0.25	4	4.3	23	5.23
AN018.020.01.008.00B	1x8.0	64/0.4	4.6	5	29	3.97
AN018.020.01.010.00B	1x10.0	77/0.4	5.3	6	43	3.03
AN018.020.01.012.00B	1x12.0	96/0.4	5.8	6.5	50	2.53
AN018.020.01.016.00B	1x16.0	126/0.4	6.4	7.2	63	1.93

物料编号	规格	导体结构	外径下限 mm	外径上限 mm	近似重量 kg/km	导体电阻 Ω/km
AN018.001.01.000.50B	1x0.50	18/0.19	2	2.3	8	37.1
AN018.001.01.000.75B	1x0.75	27/0.19	2.2	2.5	12	24.7
AN018.001.01.001.00B	1x1.00	35/0.19	2.4	2.7	15	18.5
AN018.001.01.001.50B	1x1.50	31/0.25	2.7	3	20	12.7



AN018.001.01.002.00B	1x2.00	41/0.25	2.9	3.2	26	9.42
AN018.001.01.002.50B	1x2.50	51/0.25	3.3	3.7	32	7.6
AN018.001.01.0003.00B	1x3.00	61/0.25	3.5	3.9	37	6
AN018.001.01.004.00B	1x4.00	82/0.25	4	4.4	49	4.71
AN018.001.01.006.00B	1x6.00	123/0.25	4.6	5	68	3.14
AN018.001.01.010.00B	1x10.00	77/0.4	6	6.5	117	1.82
AN018.001.01.016.00B	1x16.00	126/0.4	7.5	8.3	193	1.16
AN018.001.01.025.00B	1x25.00	189/0.4	9.5	10.4	274	0.74
AN018.001.01.035.00B	1x35.00	266/0.4	10.6	11.6	397	0.53
AN018.001.01.050.00B	1x50.00	380/0.4	12.9	13.5	547	0.37
AN018.001.01.070.00B	1x70.00	532/0.4	14.8	15.5	769	0.26
AN018.001.01.095.00B	1x95.00	722/0.4	17	18	990	0.2
AN018.001.01.120.00B	1x120.00	925/0.4	18.7	19.7	1250	0.15